

## **PRODUCT INFORMATION**

### **EMULSIFIER 1512:-**

- We are engaged in offering an elite variety of Emulsifiers for Soluble cutting oils and antistatic Coning oils.
- Emulsifier 1512 is an emulsifier for making soluble cutting oils giving milky white emulsion, which is stable up to 750 ppm hardness of water.
- Emulsifier 1512 can be used for formulating soluble cutting oils with LVI/HVI or Naphthenic oils and its blends.

### **BENEFITS**

- EXCELLENT ANTI BACTERIAL PROPERTIES.
- GOOD HARD WATER STABILITY.
- LOW FOAMING.
- EXCELLENT CORROSION PREVENTION.
- GOOD LUBRICATION AND HEAT REMOVAL.

CHARACTERISTICS	SPECIFICATIONS
Appearance	Reddish Brown Liquid
Specific Gravity @ 29 ° C	0.99 to 1. gm./c.c.
Emulsion pH	9.0 to 9.5
Flash Point	150.0 ° C.
Dosage	15 % to 20% w/v
Copper Corrosion	Pass

*The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.*

*We assume no liability for the completeness of it or errors in it.*

**A-406, Kailash Esplanade, L.B.S. Marg, Ghatkopar (West), Mumbai – 400 086.**

**URL: <https://www.hitechpetrochem.com> Mob. Tel.: 9821385015 / 9223385015.**