

PRODUCT INFORMATION

HI-CUT 14:-

- HI-CUT 14 forms a milky white emulsion with water and contains rust inhibitor to impart anti-rust, anti-corrosion properties and a biocide to prevent bacterial growth in the water emulsion.
- This oil has superior cooling and lubricating properties, which impart excellent surface, finish and minimize tool wear.
- HI-CUT 14 is normally used as the concentration of 7-8 %. For the grinding and other light operations more dilutions are required; depending on the job in hand.
- HI-CUT 14 is to be added to water with continuous stirring and not the vice versa, to get stable emulsion.
- HI-CUT 14 is free of chlorine additive, which makes it eco-friendly.
- HI-CUT 14 meets the performance level of IS 1115-1985 and is recommended for a variety of operations on ferrous and non-ferrous metals.

CHACTERISTICS	SPECIFICATIONS
Color	Amber.
Emulsion	Milky white.
Viscosity @ 40 ° C	20 cSt.
Flash Point, min.	150.0 ° C.
Frothing Test	Pass.
Cast Iron Corrosion	Pass.
pH of 2% Soln., min.	9.0
Dilution Test	Pass.

*The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.
We assume no liability for the completeness of it or errors in it.*

A-406, Kailash Esplanade, L.B.S. Marg, Ghatkopar (West), Mumbai – 400 086.

URL: <https://www.hitechpetrochem.com> Mob. Tel.: 9821385015 / 9223385015.