

PRODUCT INFORMATION

HI-HON 47:-

- HI-HON 47 is a medium viscosity honing oil based on the mixture of highly refined lubricating oils.
- It is a mixture of specially selected lubricating oils, EP and oiliness additives in a balanced manner to give excellent flushing properties, which promote rapid sedimentation of foreign matters.
- HI-HON 47 is free of chlorine-based additives, making it environment friendly.
- The selected combination of additives reduces oil mist compared to conventional cutting oils.
- HI-HON 47 is universal honing oil suitable for normal and hardened steels, grey cast iron, hard chrome surfaces, non-ferrous metals, etc.

CHARACTERISTICS	SPECIFICATIONS
Viscosity @ 40 ° C	10 – 12 cSt.
Specific Gravity @ 29 ° C	0.835 ± 0.05 gm/c.c.
Colour	2.0 Max.
Flash Point	155 ± 5° C.
Total Acid Number	1.0 mg. KOH/gm.
Saponification Number	20 ± 5 mg. KOH/gm.
Copper corrosion	1b

*The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.
We assume no liability for the completeness of it or errors in it.*

A-406, Kailash Esplanade, L.B.S. Marg, Ghatkopar (West), Mumbai – 400 086.

URL: <https://www.hitechpetrochem.com> Mob. Tel.: 9821385015 / 9223385015.