

## **PRODUCT INFORMATION**

### **HI- SPIN 40:-**

HI-SPIN 40 is a combination of lubricants and surfactants for processing of polypropylene yarn i.e. MFY & BCF.

#### **Features:**

- Imparting low fiber to metal and fiber to ceramic dynamic friction and high filament cohesion to have good package build up and avoid overthrown ends or loops.
- Good antistatic & non corrosive properties.
- Low filament to filament dynamic friction improves draw ability and reduce filament breakages in subsequent process.
- Stable thermal characteristics and easily washable by water

#### **Special Features:**

- It is Spin Finish Specially formulated for Polypropylene MFY production lines.
- Offers high level of antistatic protection.
- Extremely low fiber / Metal & Fiber / Ceramic friction.
- Has an excellent wetting power for homogeneous film formation.
- Good thermal stability.
- No hot roll deposits.
- Suitable for rolling and nozzle lubrication and be used as Neat.

CHARACTERISTICS	SPECIFICATIONS
Appearance	Clear Liquid
Color (Gardner)	Max. 4.0
Viscosity @ 40 ° C	40 ± 10
Appearance of 10 % Emulsion	150. 0 ° C.
pH of 10% Emulsion	7.5 ± 0.5
Acid Value	Max. 4.0
Density @ 30 ° C	1.08± 0.05
Active Content	85 ± 2

*The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.  
We assume no liability for the completeness of it or errors in it.*

**A-406, Kailash Esplanade, L.B.S. Marg, Ghatkopar (West), Mumbai – 400 086.**

**URL: <https://www.hitechpetrochem.com> Mob. Tel.: 9821385015 / 9223385015.**