

Speciality Lubricants, Additives, Coolants

## **PRODUCT INFORMATION**

## **RUSTNIL - 8:-**

This product is mobile liquid consisting of thin oily film forming ingredients, rust inhibitors and water displacing additives in special solvents and best quality mineral oils. On evaporation of solvent, thin soft oily film is obtained.

The water-displacing additives displace all the traces of moisture on the coated components, leaving a protective film of these products.

RUSTNIL – 8 is premium rust preventive and is specially designed as a protective for all types of bearings and tools. Its superior characteristics protect the components for extended durations. It can be used for dual purpose– for inter process treatments as well as for application on the protection parts at the final package stage. For final application the product can be used as such, whereas it can be diluted with mineral turpentine for inter process treatments to cut down the costs.

These products can be applied by spray OR cold dip method.

## **SPECIFICATIONS: -**

| CHACTERISTICS                           | SPECIFICATIONS |
|---|----------------|
| Flash Point ° C                         | 60             |
| Copper strip corrosion 3 hrs. @ 100 ° C | 1.0            |
| Water displacement test                 | Pass           |
| Finger print Neutralisation             | Pass           |
| Coverage sq.mt./lit.                    | 75             |
| Indoor Protection                       | 6-8 momths     |
| Outdoor Protection                      | 3-4 months     |
| Protection(Packed Goods)                | 12 months      |

The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.

We assume no liability for the completeness of it or errors in it.