

PRODUCT INFORMATION

SUPER CUT 4:-

- SUPERCUT 4 is specially formulated semi synthetic cutting/grinding oil suitable for all application like cutting, grinding, tapping etc.
- SUPERCUT 4 is made from selected mineral and vegetable oil combination and performance enhancing additives.
- It contains no sulfur or chlorine additive making it user friendly in nature.
- It is useful for metals and all operations like drilling, boring or milling operations.
- It is also suitable for precision lathes work on high speed machines where there is an alternating requirement for production of ferrous and non-ferrous metals.
- It is also suitable for grinding operations.

Performance Benefits:

- Excellent Flushing Action.
- Fast Swarf Clearance.
- Good Antiweld Properties.
- Excellent tool Life.
- Minimized Wear.
- Economy in Usage as it can be used by dilution with water.

CHARACTERISTICS	SPECIFICATIONS
Appearance	Clear Amber Fluid.
Sp. Gr. @ 30° C	0.97 ±0.05
Kinetic.Viscosity. @ 40° C, cSt.	70 ± 5
Flash Point (Open Cup) ° C	N.A.
Dilution	1 to 8 % depending on the operation
Qualifications	Suitable for all metals

*The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.
We assume no liability for the completeness of it or errors in it.*

A-406, Kailash Esplanade, L.B.S. Marg, Ghatkopar (West), Mumbai – 400 086.

URL: <https://www.hitechpetrochem.com> Mob. Tel.: 9821385015 / 9223385015.