

PRODUCT INFORMATION

SUPER SYNTH 4:-

Features :-

- SUPERSYNTH 4 is a specially developed coolant for the users of Diamond grinding wheels.
- It is user friendly in nature and it does not rust non-ferrous metals including Tungsten Carbide.
- Due to specially developed chemicals it gives perfect finish and lasts for longer times.
- Special additives also increase the wheel dressing period, resulting in increased life of costly diamond wheels.

Salient Features:-

- Confirms to IS: 11186-1985 standards.
- It does not contain ANY oil.
- It does not rust machine at all.
- It does not leave any mark on work piece viz. Tungsten Carbide.
- It cools the grinding zone much effectively as specially developed coolants are incorporated.
- Bacteria formation is almost completely eliminated.
- It settles the dust very fast as dispersing agents of high activity are added; resulting in work piece of precision.
- It is user friendly in nature, as it does not affect the machine or the workman in any manner whatsoever.

CHARACTERISTICS	SPECIFICATIONS
Nature	Clear, Yellowish orange liquid
Sp. Gr. @ 25° C	1.15
pH of 10% sion.	9.0 to 9.5
Low Tempt. Stability	Pass
Oil Content	NIL
Emulsion	Fully clear, Fluorescent green
Effective life of emulsion	1 ½ to 2 months
Qualifications	Suitable for non-ferrous metals including Tungsten Carbide
Dilution Ratio (SS4: Water)	1:30 to 1:50 for most of the operations
Handling Instructions	NIL

*The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.
We assume no liability for the completeness of it or errors in it.*

A-406, Kailash Esplanade, L.B.S. Marg, Ghatkopar (West), Mumbai – 400 086.

URL: <https://www.hitechpetrochem.com> Mob. Tel.: 9821385015 / 9223385015.