

Speciality Lubricants, Additives, Coolants

## **PRODUCT INFORMATION**

# SUPER SYNTH 9:-

### **FEATURES:-**

- SUPERSYNTH 9 is clean and uniquely bio-resistant, which assures long, odour-free sump life unequalled by conventional bio-stable and other water soluble fluids.
- SUPERSYNTH 9 is fully synthetic grinding fluid without any traces of Nitrite making it Eco friendly in nature, ensuring environment safety and user health.

### **DESCRIPTION:-**

• SUPERSYNTH 9 is completely inhibited against attack on cobalt. Dilutions of this product will protect your inserts and reduce health hazard potentials, and generation of toxic wastes.

### **HOW TO USE:-**

- The recommended usage concentration of SUPERSYNTH 9 may be customized to suit individual needs or solutions, which may vary from time to time.
- We strongly advises that you contact our Sales Representative to discuss before commencement of use.

CHARACTERISTICS	SPECIFICATIONS
Appearance	Yellow liquid
Sp. Gr. @ 15° C	1.068 kg/L
pH of 5% soln.	9.0 ± 0.1
Oil Content	NIL
Emulsion	Colourless
Effective life of emulsion	3 to 4 months
Qualifications	Suitable for non-ferrous metals including Tungsten Carbide

The information provided on this page is, to the best of our knowledge accurate, however, it is subject to change without prior notice.

We assume no liability for the completeness of it or errors in it.